



Product Feature

Recessed downlight

Aluminium die cast ceiling trim, powder painted

Aluminium die cast housing, powder painted

Basic colors: white, black, silver

RAL colors on demand

Flat transparent tempered glass

High purity anodised aluminium reflector

Remote electronic driver included (dimming driver on demand)

The LED light source is of different manufacturers applicable

Passive cooling: heat dissipation via alu.heat sink

Technical Data

| Product Code | Light Source | Luminous Flux | Power | Color Temperature | CRI | Beam Angle | L(mm) | H(mm) | Cutting Hole(mm) |
|--------------|--------------|---------------|-------|-------------------|-----|------------|-------|-------|------------------|
| LD533 | COB | 696lm | 9W | 3000K,4000K | >80 | 40°,60° | Φ110 | 43 | Φ95 |
| LD534 | COB | 1105lm | 15W | 3000K,4000K | >80 | 40°,60° | Φ140 | 54 | Φ120 |
| LD535 | COB | 1678lm | 22W | 3000K,4000K | >80 | 40°,60° | Φ162 | 64 | Φ140 |
| LD536 | COB | 2252lm | 30W | 3000K,4000K | >80 | 40°,60° | Φ193 | 76 | Φ165 |
| LD538 | COB | 2436lm | 33W | 3000K,4000K | >80 | 40°,60° | Φ230 | 88 | Φ200 |