



## Product Feature

Flood light

Aluminium die cast fitting, powder painted

Basic colors: black, silver

RAL colors on demand

Flat transparent tempered glass

High purity anodised aluminium reflector

Electronic driver embedded

The LED light source is of different manufacturers applicable

Passive cooling: heat dissipation via alu.heat sink

## Technical Data

Product Code	Power	Light Source	Luminous Flux	Color Temperature	CRI	Beam Angle	L1(mm)	L2(mm)	H(mm)
<b>ACE10W</b>	<b>10W</b>	<b>SMD</b>	<b>900lm</b>	<b>3000K-6000K</b>	<b>&gt;70</b>	<b>120°</b>	<b>113</b>	<b>160</b>	<b>53</b>
<b>ACE30W</b>	<b>30W</b>	<b>SMD</b>	<b>2700lm</b>	<b>3000K-6000K</b>	<b>&gt;70</b>	<b>120°</b>	<b>177</b>	<b>230</b>	<b>68</b>
<b>ACE50W</b>	<b>50W</b>	<b>SMD</b>	<b>4500lm</b>	<b>3000K-6000K</b>	<b>&gt;70</b>	<b>120°</b>	<b>223</b>	<b>310</b>	<b>80</b>
<b>ACE100W</b>	<b>100W</b>	<b>SMD</b>	<b>9000lm</b>	<b>3000K-6000K</b>	<b>&gt;70</b>	<b>120°</b>	<b>335</b>	<b>435</b>	<b>120</b>
<b>ACE200W</b>	<b>200W</b>	<b>SMD</b>	<b>18000lm</b>	<b>3000K-6000K</b>	<b>&gt;70</b>	<b>120°</b>	<b>405</b>	<b>505</b>	<b>150</b>

The IES files and test report will be offered by request